

Giga Voip 4 PORT FXO/FXS VoIP GATEWAY



SPECIFICATIONS

Model	Channels
GN-VOIP-FXS-4	4FXS
GN-VOIP-FXO-4	4FXO
GN-VOIP-4FXS4FXO	4FXS4FXO

Dimension(L*W*H)	242*152*40mm
Weight(unit:kg)	1.1
Operating temperature	0-40
Storage temperature	-20-70
Operating humidity	10%-90%
External power adapter	yes
Power input	220VAC/50Hz/0.5A
External power input	12VDC,2A
Power Consumption	15w
Network interface	10/100BASE-TX
Number of WAN ports	1
Number of LAN ports	3



Features

- Primary and secondary SIP account
- Flexible set port group
- IP trunk
- Flexible routing and manipulation
- Data/ Voice/ Management VLAN
- Voice /FAX/Modem
- SNMP
- Firmware update automatically /configure update

Specification

Physical Interfaces

- Phone Interface: 4 FX/FXO, RJ-11
- Ethernet Interface: 2* RJ-45 10/100Mbps, RJ-45
- LED Indicators: Power, Run, Network and Line LEDs

Voice Processing

- Voice Codec: G.711A/U law, G.723.1, G.729A/B
- Voice Packet Capabilities: CNG, VAD, G.168, A/B
- Programmable Gain Control
- DTMF mode: Signal/RFC2833/INBAND

Call Features

- Calling Type: Voice/ T.38/Pass-through/Modem FAX mode, Up to 14.4kbps

- IVR Voice Prompt: Private service IVR
- Telephony Features: Call waiting, Call transfer(Blind transfer, Attend Transfer , Half blind transfer), Quick pick, Call forwarding, Hotline, Call hold, DND, Voice mail, 3-way conference, Direct IP address call

Network

- Network Protocols: IP, TCP, UDP, TFTP, FTP, ARP, RARP, Ping, NTP, SNTP, Http, DNS, Tracert
- NAT Traversal: STUN, Ping, Tracert

Protocol and Standard

- Protocol: SIP V2.0 (RFC 3261, 3262, 3264), RTP/RTCP
- Standard: Bellcore Type 1 & 2, ETSI, BT, NTT and DTMF based CID, configurable call progress tone

Configuration Management

- Auto Provisioning: TFTP, HTTP, Auto configure/upgrade, Syslog and CDR, SNMP
- Web GUI: Configuration, firmware upgrade, TCP/UDP/Current RTP/History calls statistics

APPLICATION:

