

Product overview

The Giganet 39U Network Cabinet is packed with features designed to simplify rack equipment installations and rack equipment maintenance: top and bottom cable routing ports, perforated door and side panels to promote efficient airflow, adjustable vertical mounting rails and more. This network cabinet allows keeping the networking equipment and many important devices attached in a firm, fixed position, contributing to ensuring stable operation.



Product Features

FEATURES
Elegance look, profound technical, precise dimension with modern taste.
Maximum loading 650kg.
Wire path on the top and bottom can be closed
Install caster and support at the same time.
Optional bottom seat for stable stand, bottom wiring, bottom cold ventilation.
Side door and rear / front door can be taken down easily.
Can be customized to individual requirements
Mounting rails are marked with "U" identification
Detachable composite structure, more convenient for being shipped
Supplied as Flat Packed

Ordering Information

PART NUMBER	PRODUCT DESCRIPTION
GN-002-6639	Giganet 39U Width 600mm Depth 600mm Glass Door Cabinet
GN-002-6839	Giganet 39U Width 600mm Depth 800mm Glass Door Cabinet
GN-002-8839	Giganet 39U Width 800mm Depth 800mm Glass Door Cabinet

Specifications

SPECIFICATIONS	
Parameters	Values
Height (U size)	39U
Width (mm)	600, 800
Depth (mm)	600, 800
Max Load (kg)	650
IP Rating	IP-20
Colors	Standard Black–RAL 9005 and Grey-RAL 7035
Lock Type	Front Door: Swivel Lock Side Panel: Small round lock
Panel Thickness (mm)	Front Panel: 1.2 Side Panel: 1.2
Frame Thickness (mm)	1.5
Standards	ANSI/EIA RS-310-D, IEC297-2, DIN41494; PART1, DIN41494; PART7, GB/T3047; 2-92 STANDARD
Side Panels	Removable Solid Panels
Front Door	Single Glass Door
Rear Door	Solid Panel

ASSEMBLED CABINET OUTER DIMENSIONS			
Parameters	GN-002-6639	GN-002-6839	GN-002-8839
Height (mm)	1921	1921	1921
Width (mm)	600	600	800
Depth (mm)	600	800	800
Weight (kg)	95	100	105

Schematics

