



Main	Description	
Input	Nominal Voltage	230V
	Frequency	50/60Hz
	Plug type	IEC60309 16A
	Max input current	16A
	Rated input current	16A
Output	Nominal Voltage	230V
	Max output current	16A
	Output Connections	8 x IEC 320 C13; 01 x IEC 320 C19
Metering & Switching	Transfer Time	10-16ms
	Overload Protection	None
	Alerts	Voltage, Current threshold, Power Source A/B power failure
	Monitoring Parameters	Voltage (V), Current (A)
	Metering Accuracy	+/- 1%
	Access	Hyper Terminal, SMNP V1, Https/Https Telnet only for NMC Module
Physical	Product Dimensions (HxWxD)	482.6x220x44.4mm
	Box Dimensions (HxWxD)	525x405x105mm
	Product Weight	3.5 kg
	Box Weight	4 kg
	Mounting Style	2 End Brackets
	Mounting Distance	465mm
	Color	Black
	Rack Space	1U
Environmental	Operating Temperature	0~45°C
	Operating Relative Humidity	5%~95%
	Operating Elevation	0~3000 meters

Part Number	Description
GN-TS-128H0912	Rack Power Transfer Switch, 1PH, 230V AC, 16A (16A rated); 9 outlets: 8x C13, 1x C19