



Main	Description	
Input	Nominal Voltage	230V
	Frequency	50/60Hz
	Plug type	IEC60309 32A
	Max input current	32A
	Rated input current	32A
Output	Nominal Voltage	230V
	Max output current	32A
	Output Connections	16 x IEC 320 C13; 02 x IEC 320 C19
Metering & Switching	Transfer time	10-16ms
	Overload Protection	Yes
	Alerts	Voltage, Current threshold, Power Source A/B power failure
	Monitoring Parameters	Voltage (V), Current (A)
	Metering Accuracy	+/- 1%
	Access	Hyper Terminal, SMNP V1, Https/Https Telnet only for NMC Module
Physical	Product Dimensions (HxWxD)	482.6x220x88.8mm
	Box Dimensions (HxWxD)	530x455x155mm
	Product Weight	4 kg
	Box Weight	4.5 kg
	Mounting Style	2 End Brackets
	Mounting Distance	465mm
	Color	Black
	Rack Space	2U
Environmental	Operating Temperature	0~45°C
	Operating Relative Humidity	5%~95%
	Operating Elevation	0~3000 meters

Part Number	Description
GN-TS-22H1822	Rack Power Transfer Switch, 1PH, 230V AC, 32A (32A rated); 18 outlets: 16x C13, 2x C19