

Giganet NGX SPLICING cassettes are designed for splicing up to 24F in a cassette. The NGX cassettes are designed to easily plug into Giganet NGX 1U 6 slot panel and each chassis can populate up to 144F with LC and 72F with SC. The cassettes are preloaded with adaptors and pigtailed supplied with splicing accessories.

FEATURES

- Conform to IEC, EIA-TIA, and Telcordia performance requirements
- Available in 12F and 24F options
- Available in Single and Multimode options
- RoHS, REACH & SVHC compliant, Materials Conflict compliant
- Flame retardant ABS+PC material

Application

- Telecommunication networks
- Data centers, Co-location DC
- LAN or Campus wide Network
- Broadband network
- Supports SFP, QSFP, CFP applications
- ➤ 100G to 10G/ 40G to 10G transition

Specifications

FOOTPRINT	LGX
MATERIAL	ABS + PC
HOUSING COLOUR	BLACK
APPLICATION	LGX PANELS, CHASSIS, WALL BOXES
FIBER CAPACITY	24FO in LC / 12FO in SC
SPLICE HOLDER	40MM Heat shrink sleeves, Available in Crimp Style or Ribbon
WEIGHT KG	0.25

Specification					
DUfUa YHYfg	I b]rg	GA 'A DC	GA '@7#G7	A A 'A DC	A A '@7#G7
5j [#A UI '@ 'GHJbXUFX	X6	Q '\$"&) # \$" +)	Q '\$"&#\$" \$	Q '\$"* \$	Q '\$"% # \$" \$
FYh fb`cgg fD7 #5D7L	X6	≥ * \$	≥ * \$#)	B5	B5
5j [#A UI '@ 'DfYa]i a	X6	Q '\$"%\$#")	Q '\$"%&#\$"%)	Q '\$"%\$#")	Q '\$"%&#\$"%)
FYh fb`cgg fD7 #5D7L	X6	≥ * \$	≥ * \$	B5	B5

ORDERING INFORMATIONS

Part Number	Description
GN-NGXSP01	Giganet NGX Splice Module for 24FO LC SM Incl. Pigtails SM G657A1 TB LSZH
GN-NGXSP02	Giganet NGX Splice Module for 24FO LC/APC SM Incl. Pigtails SM G657A1 TB LSZH
GN-NGXSP03	Giganet NGX Splice Module for 24FO LC MM Incl. Pigtails OM4 RBS TB LSZH
GN-NGXSP04	Giganet NGX Splice Module for 12FO SC SM Incl. Pigtails SM G657A1 TB LSZH
GN-NGXSP05	Giganet NGX Splice Module for 12FO SC/APC SM Incl. Pigtails SM G657A1 TB LSZH
GN-NGXSP06	Giganet NGX Splice Module for 12FO SC MM Incl. Pigtails OM4 RBS TB LSZH

